

CA-5116-S1

Category : 5 IN 1 DVR

Hits : 23

Brief :

Features

Support H.264+ (Quasi H.265) encoding, ultra-low bitrates, compatible with H.264 surroundings

Support AHD-H series front-end non-real-time encoding

Support AHD/TVI/CVI/CVBS/IP Self-adaptive

Support VGA, HDMI HD output

Support mobile Phone monitoring (IOS, Android) <



Description

Inquiry

PDF

	Model	CA-5116-S1
System	Main processor	Hi3531A
Video	video codec	H.264+ (Quasi H.265) /H.264
	Encode	16*4M@8fps(AHD)/ 16*3M@10fps(AHD)/16*1080P @15fps (5 in 1) / 16*720P(5 in 1)
	Decode	8*4M@8fps(AHD)/ 8*3M@10fps(AHD)/8*1080P @15fps (5 in 1) / 8*720P(5 in 1)
	Multi-mode input	Pure Analog: 16*4M; Hybrid: 8*4M (analog) +8*4M (network) Pure Network: 8*3M ;4*5M
Audio	Audio compression	G.711A
	Intercom	support
Recording and Playback	Record mode	Manual>alarm>motion detection>timing
	Playback Channels	8ch
Storage and backup	Backup mode	Network backup、 USB HDD, USB writer、 SATA writer
Interface	Video input	16ch BNC
	Video output	1ch VGA,1ch HDMI
	Audio input	2ch RCA
	Audio output	1ch RCA
	Alarm input	16CH
	Alarm output	4CH
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1* RS485; support multiple PTZ protocols
	USB	2 USB ports
	Hard disk	2SATA (Each maximum support 8T)
	Wireless	3G、 WIFI(expand via USB)
Other	Power	12V/5A
	Dimension	350mm(length)* 296mm(width)* 44mm(high)