

CA-8016/8032 NVR

Category : NVR H.265/H.264

Hits : 33

Brief :

H.265 / H.264 video formats

Up to 8MP IP camera can be accessed

HDMI at up to 4K,VGA up to 1080P

All channel real-time synchronous playback

Support IE, Chrome, Firefox, Safari, and browser plug-in free



Description

Inquiry

PDF

	Model	CA-8016 NVR	CA-8032 NVR
System	Main processor	HI3536	
	Operating System	Embedded Linux	
	System Resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup	
Operator Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation	
	Preview	1/4/8/16/24/32	
Video	Video input (IP)	8*5M/16*3M/32*1080P	
	Video standards	PAL(625TVL,50f/s) ; NTSC(525TVL,60f/s)	
	Video compression	H.265/H.264	
	Display quality	Max:4K (support 1920*1080, 1280*720,1440*900,1280*1024, 1024*768,800*600)	
	Playback quality	5M/3M/1080P	
	Decode	4*5M/8*3M/4*1080P	
	Motion detection	Depend on camera	
Audio	Audio compression	G.711A	
	intercom	Support	
Record & playback	Recording mode	Manual>Alarm>Video Detection>Continuous	
	Local Playback	4*5M/8*3M/4*1080P	
	Search mode	search by Time/calendar/event/channel	
Storage & Backup	Record Storage	HDD , network	
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner	
Interface	Video output	1ch HDMI ,1ch VGA output	
	Audio I/O	1/1	
	Alarm I/O	No (Can customized 16/4 alarm i/o)	16/4
	Network interface	1*RJ45 10M/100M /1000MAdaptive Ethernet port	
	USB interface	1*USB2.0 port,1*USB3.0 port (Reserved 2 pre interface)	
	Hard disk	4SATA(Up to 6TB for each disk)	8SATA (Up to 6TB for each disk)
other	PTZ control	Control PTZ device by network	
	ONVIF	Support	
	Power supply	12V/6A	ATX
	Power Consumption	<10W(Without HDD)	
	Work environment	Temperature:0℃- + 55℃ , Humidity:10% - 90%RH , Atm:86kpa - 106kp	
	dimension	192.5mm(H)*127mm(W)	
	weight	Around 220g	