



securitysalesmanager@caddx.us

www.caddx.us +1(315) 409719

Head Office and R&D Team:
Add: 314 East Fayette Street,
Syracuse, NY, USA 13202

CADDX SYSTEMS INC.

NVR 36CH 4K / 4HDD



CA-8036kNVR

Features :

1. Support H.265+/H.265/H. 264
2. Support 4K , 5M , 4 M, 2M
3. VGA, HDMI output simultaneously
4. **NEW TECHNOLOGY** Support **NEW Smart function** for industrial refrigerators temperatures, humidity, controls Gates, **Others**....
- 5 .Cloud service www.caddxcloud.net , ,support Google cloud server, P2P, Alarm pushing
- 6 . Multiple network services DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G,WIFI
- 7 . cell phone access supported (IOS, Android) caddx.us.smart
- 8.IE internet explorer Browser access supported
- 9 . More than twenty kind of language
- 10.Multiple platform : WEB, CMS, VMS, Caddx APP

Technical Parameters :

Model number		CA-4k8036NVR
System	Main processor	HI3536C-4G
	OS	Embedded LINUX
	Build in POE	NOT Supported
	PROTOCOLS	ONVIF / Caddx.us Protocols
Video Record	VIDEO INPUT	16CH*4K /36*5M /25fps / 4M / 2M
	Video compression	H.265+/H.265/H.264
	Video standards	PAL /NTSC
	Display Quality	Simple window: 1*5M /25fps, Multiple window: 9*D1/15fps
	MOTION DETECION	Depend in the camera
RECORD & PLAY BACK	Record Mode	Manual>Alarm>Motion detection>Timing
	Record Query	Time point、Calendar、Event、Chanel
	Record storage	Local hard disk、Network
	Backup Mode	Network、USB disk
Interface	Video output	1*HDMI, 1*VGA
	Network interface	1*RJ45 10M/100M /1000M self-adaptive
	AUDION I/O	No
	USB INTERFACE	2*USB2.0
Others System	PTZ CONTROL	CONTROL PTZ Devices by network
	HDD	4*SATA (each max 8T)
	Working temperature	0°C- +55°C
	Working Humidity	10%--90%
	Power Supply	12VDC/7A
	Size	400mm (Length) *350mm (Width) 60mm (Height)
	WEIGHT	Around 900g